

2023 Product Guide

	Northeast Pro-Series	Slocomb Harmony 100	Slocomb Protech 400	United 9600 series	Trimline DR200	Andersen 400 Woodwright
	Sturdy and well designed Nice Asthetics heavy duty extruded screen frame	Sleek design together with rugged engineering make this the best looking & durable performer	Hurricane rated DP 50 Sturdy and well designed InnergyTM Rigid Thermal Reinforcement:	This window replicates the look of a wood window with a unique and durable design featuring a welded vinyl frame and a solid core cellular PVC sash for a timeless visual appeal	For the purist, this wood window offers the closest thing to the original wood window it is to replace	This timeless window is a best-seller Andersen's is second to none. Used for historic and traditional homes. Natural wood interior Patented Fibrex exterior
Grade	Structural Grade Rating DP 40	Structural Grade Rating DP 35	Structural Grade Rating DP 50 <i>Light Commercial rated</i>	Performance Class LCPG40-H <i>Light Commercial rated</i>	Structural Grade Rating DP LC 45 <i>Light Commercial rated</i>	Insert style frame DP 25 Full (new construction) DP 50
Frame	Welded PVC multi-chambered	Welded multi chambered PVC multi chambered PVC Integral ant-bow sill interlock	Welded multi chambered PVC InnergyTM Rigid Thermal Reinforcement magnetic bottom seal	Composite window welded vinyl frame and a solid core cellular PVC sash	dovetailed pine corners with aluminum clad	dovetailed pine corners with Fibrex Clad exterior
Glass	7/8" double pane Low E/Argon Gas PPG Intercept Spacer	3/4" double pane Low E/Argon Gas Duralite high efficiency spacer Improved condensation resistance Superior argon gas retention Unique patented design Exceeds ENERGY STAR	7/8" double pane Low E/Argon Gas Duralite high efficiency spacer Improved condensation resistance Superior argon gas retention Unique patented design Exceeds ENERGY STAR	3/4" double pane Low E2/Argon Gas High performance Stainless Steel Intercept Spacer Exceeds ENERGY STAR	7/8" double pane Low E/Argon Gas Super spacer dual seal technology - acrylic seal with a barrier seal Comfort Plus technolgy Balanced year round performance Exceeds ENERGY STAR	5/8" double pane Low E/Argon Gas High performance Stainless Steel spacer Exceeds ENERGY STAR
Balance System	constant force	constant force	constant force	constant force	block & tackle	block & tackle
Grids (optional) inside glass	5/8" contour grids	5/8" contour grids	5/8" contour grids	5/8" contour inside glass or simulated divided lites	5/8" contour inside glass or simulated divided lites	Up to 9 hardware finish options custom grille patterns
Screen	Extruded alum frame - fiberglass mesh	Extruded alum frame - fiberglass mesh	Extruded alum frame fiberglass mesh	Roll form fiberglass mesh	Extruded alum frame - fiberglass mesh	Extruded alum frame - fiberglass mesh
Warranty	life frame- 20 yrs Glass Non Transferable	lifetime - transferable Non Pro rated and Transferable Good Housekeeping Seal & Warranty	lifetime - transferable Non Pro rated and Transferable Good Housekeeping Seal & Warranty	lifetime - transferable Non Pro rated and Transferable	10yrs-frame/20-glass Transferable	10yrs-frame/20-glass Transferable
options:	bright white	soft white & almond	soft white & almond	Soft white	pre- painted interior	pre- painted interior
Colors:		Exterior Laminate colors Black - bronze - brown laminate or painted exterior	Exterior Laminate colors Black - bronze - brown laminate or painted exterior	Black co-extruded inside & out Black ext.(painted) w/white interior	Exterior colors: White - Beige - Brown Black - Green	7 exterior colors with 3 natural wood interiors
Energy efficiency	U Value = .30	U Value = .27	U Value = .26	U Value = U.27	U Value =.30 Comfort E -.27 Comfort e Plus	U Value = U.27
Min - max sizes	w 15.25"-53" h-23.75"-86"	w -14.25"-54" h - 20.5 -85 max 124ui	W-12.75 - 58" h- 20 - 106 max 140	W - 19 3/4" - 48" H- 25.25" - 80"	w -14"-48" h - 24 -84 max 132ui	w 16.5"-45.5" h 32"-76.875"